



CIT LTDA

COMPAÑÍA INTERNACIONAL DE TELECOMUNICACIONES

TELECOMUNICACIONES
ELECTRÓNICA - TELEFONÍA – COMPUTACIÓN
RUT N° 78.856.630 - 1

Medidor CO TM-801



CO Measurement:	
Range	0 ~ 1000ppm
Resolution	±1ppm
Accuracy	±5% + 2ppm
Repeatability	< 2%
Response time※	< 30 seconds.
Zero drift in long term	< 5ppm
Sensitivity drift	< 5% (per year)
Typical sensor life	3 years

Temperature Measurement:	
Range	-20~50°C/-4~122°F
Resolution	±0.1°C/±0.1°F
Accuracy	±1.0°C/±1.8°F

- Backlit 4 dgt LCD with maximum 1000 counts.
- Sample rate: 1 time/second
- Max/Min/Average Hold.
- Data Hold.
- Low battery indication
- Auto power off with disable function.
- Adjustable alarm.
- Sample rate: 1 time/second.

Power supply :	1.5V UM-4(AAA) battery × 6 PCS or AC100~240V or DC Adaptor 9V/0.5A(9mm).
Battery life:	Approx 90 hours.
Operating Temperature & Humidity:	(-20°C to +50°C)
Storage Temperature & Humidity :	(-10°C to +50°C, <70% RH.)
Dimension:	156×73×35mm(LxWxH).
Weight:	approx 250g (Batteries not included).
Standard accessories:	UM-4(AAA)1.5V battery ×6 PCS, user's manual.