PRIL **Moilbe Router Specification** ſ

I

I

I

I



BPR1000

is 3G/3.5G Mobile Router will offer subscribers of wireless carriers the ability to share Mobile Broadband access at speeds up to 3.6Mbit/s, and 802.11g connected stations from anywhere a compatible 3G/3.5G/WiMAX mobile signal is available.

BPR1000 Mobile Router is also good for ITSP, multibranch offices or SOHO & Hot Spot applications combined with wireless broadband accessing.

		-	
WWAN Characteristics		Physical Characteristics	
Standard PC Card	HSDPA / EVDO / UMTS / EDGE /	Antenna	Internal WiFi Antenna
Slot or USB Port	CMDA 1x Card / WiMAX Card	Button	EZ Secure Set
LAN Characteristics			Load Default
Standard	IEEE802.3, IEEE802.3u	Ports	PC Card Slot
Data Rate	10/100Mbps		Power Jack
WLAN Characteristics			RJ-45 Jack
Standard	IEEE 802.11b/g		USB
Frequency Range	2.4~2.497 GHz	LED	Power
Operating Channels	FCC : 1 ~ 11		WAN Link & Activity
	ETSI : 1 ~ 13		WiFi Link & Activity
	Japan : 1 ~ 14		LAN Link & Activity
Data Rate	1,2,5.5,11,18,24,36,48,54 Mbps		Status
RF Output Power	13 ~ 15dBm	Dimensions	H: 136 x W: 92 x D: 27 mm
Effect Range	Indoor : Up to 70M	Weight	275g
	Outdoor : Up to 200 ~ 250M	Accessories	
WiFi Security	WEP Key None / 64 / 128 bits	AC Adapter	External 5VDC / 2A
	WPA / WPA2	Environmental	
Router Characteristics		Temperature	Operating: 0 ~ 50 $^\circ$
Feature	DHCP Server		Storage: -30 ~ 70℃
	DMZ Support	Humidity	10% ~ 95% (Non-condensing)
	IP Sharing	Certifications	
	MAC access control	EMC/EM	FCC Class B, CE,
	Auto-Reconnect		
Provides Wireless Internet Access Anywhere at Anytime within a wireless broadband network.		ξ	3.56 /WiMA X Wireless Network
Multiple Users can share high-speed connections with rates up to 7.2Mbps .			
User Friendly configuration and Ease to Use			

Cable and DSL WiFi Router replacement at home or offices.

